

EL2 Built-in Loudspeaker 4 Ohms

4 Ohm built-in loudspeaker with volume control for emergency vehicles

Article Number

01 6601 01501157



Characteristics

- Built-in Loudspeaker with 4 Ohm
- Potentiometer for adjusting the volume
- Wide frequency range
- Closed rear volume
- Low installation depth < 30 mm

Scope of delivery

- Small loudspeaker with potentiometer and 30 cm connection cable

Options

- Customized plugs and connection cables
- 8 Ohm version with 30 cm connection cable and connector plug (01 6601 01501057)
- 4 Ohm version with 2 m connection cable and open cable (01 6601 01500157)
- 8 Ohm version with 2 m connection cable and open cable (01 6601 01500057)
- [Individual Modifications and Customisations](#) on request

Application range

- For installation in emergency vehicles
- For mobile or stationary playback of audio messages

Specifications

General

Housing	Plastic PA, gray (RAL 7001)
Dimensions	Height 120 mm, width 100 mm, depth 46 mm (installation depth 27 mm)
Weight	220 g (7.7 oz)
Connection Cable	30 cm length, 2-wire, connector
Storage Temperature	-30 °C (-22 °F) to +75 °C (+167 °F)
Operating Temperature	-25 °C (-13 °F) to +60 °C (140 °F)

Loudspeaker

Frequency Range	300 Hz to 10 kHz at -10 dB
Effective Sound Pressure	82 dB/1 W/1 m $\pm$ 3 dB
Impedance	4 Ohm $\pm$ 20 % bei 1 kHz
Maximum Output	max. 6 W