EL2 Built-in Loudspeaker 8 Ohms

8 Ohm built-in loudspeaker with volume control for emergency vehicles

Article Number

01 6601 01501057

Characteristics

- Built-in Loudspeaker with 8 Ohm
- Potentiometer for adjusting the volume
- Wide frequency range
- Closed rear volume
- Low installation depth < 30 mm

Scope of delivery

- Small loudspeaker with potentiometer and 30 cm connection cable

Options

- Customized plugs and connection cables
- 4 Ohm version with 30 cm connection cable and connector plug (01 6601 01501157)
- 4 Ohm version with 2 m connection cable and open cable (01 6601 01500157)
- 8 Ohm version with 2 m connection cable and open cable (01 6601 01500057)
- Individual Modifications and Customisations on request

Application range

- For installation in emergency vehicles
- For mobile or stationary playback of audio messages

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 10.09.2026 22:16

Specifications

General

Housing	Plastic PA, gray (RAL 7001)
Dimensions	Height 120 mm, width 100 mm, depth 46 mm (installation depth 27 mm)
Weight	220 g (7.7 oz)
Connection Cable	30 cm length, 2-wire, connector
Storage Temperature	-30 °C (-22 °F) to +75 °C (+167 °F)
Operating Temperature	-25 °C (-13 °F) to +60 °C (140 °F)

Loudspeaker

Frequency Range	300 Hz to 10 kHz at -10 dB
Effective Sound Pressure	82 dB/1 W/1 m ± 3 dB
Impedance	8 Ohm ± 20 % bei 1 kHz
Maximum Output	max. 6 W

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.