KL1 Amplified Loudspeaker

Dynamic loudspeaker with integrated amplifier

Article Number

01 6601 00400451 (former 6601-004-003-51)

Characteristics

- Loudspeaker with integrated amplifier
- Car and truck supply ready (12 V and 24 V)
- Low consumption
- Small design for easy and space-saving installation
- Frequency range optimized for radio communication

Scope of delivery

- Loudspeaker with mount and cable
- Installation guide

Options

- Minor modifications and individual adaptations on request

Application range

- For mobile and fixed radio systems

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 10.09.2026 22:46

Specifications

General	
Housing	PA plastic, black
Dimensions	Height 72 mm, width 77 mm, depth 50 mm, Ø 58 mm
Weight	235 g (8.3 oz)
Connection	5-wire cable; cable length: 2 m; open wires
Storage temperature	-40 °C to +70 °C (-40 °F to +176 °F)
Operating temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Operating voltage	10 V to 32 V
Consumption	max. 450 mA,

Loudspeaker amplifier	
Frequency range	300 Hz to 6 kHz at -10 dB
Effective sound pressure	83 dB/1 W/1 m ± 3 dB
Maximum output	3.2 W
Gain	+24 dB
Input voltage	100 mV
Input impedance	1 kOhm
Ignition contact	Yes

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.