KL1/B Loudspeaker

Dynamic loudspeaker

Article Number

01 6601 01400051 (former 2601-047-001-51)

Characteristics

- Very rugged plastic housing
- Small design for easy installation
- Frequency range optimized for hands-free systems
- Flexible mount

Scope of delivery

- Loudspeaker with cable and mount

Options

- Customized plugs and cables
- 4 Ohm version
- Minor modifications and individual adaptations on request

Application range

- For mobile and fixed hands-free systems

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 14.11.2026 12:09

Specifications

General

Housing	PA plastic, black
Dimensions	Height 72 mm, width 77 mm, depth 50 mm, Ø 58 mm
Weight	225 g (7.9 oz)
Connection	2-wire cable; cable length: 3 m, without connector
Storage temperature	-30 °C to +75 °C (-22 °F to +167 °F)
Operating temperature	-25 °C to +60 °C (-13 °F to +140 °F)

Loudspeaker

Frequency range	300 Hz to 16 kHz at -10 dB
Effective sound pressure	83 dB/1 W/1 m ± 3 dB
Impedance	8 Ohm ± 20 % at 1 kHz
Maximum output	max. 5 W

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.