KL18 Loudspeaker

Dynamic loudspeaker

Article Number

01 6601 01100051

Characteristics

- Rugged plastic housing
- Small design for easy installation
- Frequency range optimized for radio communication
- Solid retaining bracket made of metal

Scope of delivery

- Loudspeaker with cable and retaining bracket

Options

- 4 Ohm version (KL14: 6601-010-000-51)
- Minor modifications and individual adaptations on request

Application range

- For mobile and fixed radio systems

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 10.09.2026 10:54

Specifications

General

Housing	ABS plastic, black
Dimensions	Height 68.5 mm, width 74.5 mm, depth 31 mm, height with retaining bracket 74.25 mm
Weight	180 g (6.3 oz)
Connection	2-wire cable; cable length: 3.00 m, with Molex plug
Storage temperature	-25 °C to +70 °C (-13 °F to +158 °F)
Operating temperature	-25 °C to +70 °C (-13 °F to +158 °F)

Loudspeaker

Frequency range	500 Hz to 7.5 kHz at -10 dB
Effective sound pressure	86 dB/1 W/1 m ± 2 dB
Impedance	8 Ohm ± 15 % at 1 kHz
Output	norm. 4 W / max. 6 W

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.