PS12 Desktop Microphone

Desktop microphone with dynamic microphone and one button

Article Number

01 6401 04900040

Characteristics

- Rugged metal housing
- Dynamic unidirectional high-noise cancelling gooseneck microphone
- Extremely durable double switch contact

Scope of delivery

- Desktop microphone
- Strain relief

Options

- Customized plugs and cables
- Special button colours and symbols
- Microphone preamplifier
- Electret microphone mounted on 8 mm gooseneck
- Up to three buttons and LEDs
- Black housing
- Minor modifications and individual adaptations on request

Application range

- Radio and PA systems in fixed indoor applications

Accessories

- WS16 windscreen (Art.-No.: 1010-042-003-64)

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 07.10.2026 10:10

Specifications

General

Microphone head	Brass, silver
Gooseneck	Metal, silver
Housing	Metal, silver
Dimensions	Microphone head: Length 80 mm, Ø 24 mm Gooseneck: Length 200 mm, Ø 11 mm Housing: Height 32 mm, width 105 mm, depth 160 mm
Weight	650 g (22.9 oz)
Connection	Cable and plug not included
Operating and display elements	1 button, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range	150 Hz to 12 kHz at -10 dB
Directivity	Cardioid (at 1 kHz; 180° -20 dB)
Sensitivity	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.