TF1 Push-to-talk Button

Gooseneck push-to-talk button

Article Number

01 6703 00700051 (former 2703-001-000-51)

Characteristics

- Rugged housing with gooseneck
- Can be positioned for improved ergonomics
- Perfect for special vehicles
- Long life switch contact
- Mounting bracket

Scope of delivery

- Gooseneck push-to-talk button with cable
- BW2 mounting bracket

Options

- Customized plugs and cables

Application range

- Radio and PA systems in mobile and fixed applications

Accessories

- BW2 mounting bracket

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 10.09.2026 00:36

Specifications

General

Housing	PA plastic, black
Gooseneck	Steel coil with external brass winding, black
Dimensions	Length 250 mm, head Ø 19 mm, body Ø 15 mm, gooseneck Ø 11 mm
Weight	150 g (5.3 oz)
Connection	2-wire cable, 1.5 m, without connector
Operating elements	1 button, yellow
Storage temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Operating temperature	-25 °C to +70 °C (-13 °F to +158 °F)

Switch

Switching capacity	max. 24 VDC/500 mA
Life cycle	200,000
Protection class	IP40
Operating force	5 N max.

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.