TM110 TF2R Hand Microphone

Dynamic hand microphone with three buttons

Article Number

01 6109 10300405

Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Rugged, powder-coated housing
- Durable spiral cable
- Extremely durable switching contacts
- Interference field compensation

Scope of delivery

- Hand microphone with spiral cable

Options

- Protection against unintentional button presses
- Level control
- Push-button switch
- Customized plugs and cables
- Special button colours or symbols
- Minor modifications and individual adaptations on request

Application range

- Radio system in mobile and fixed applications

Accessories

- HV5 mount
- Rubber protective ring for microphone head
- Microphone preamplifier V966, V967, V856 and V857

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 10.09.2026 22:21

Specifications

General

Housing	Brass, black
Dimensions	Length 173 mm, head Ø 29 mm, body Ø 24 mm
Weight	245 g (8.6 oz)
Connection	6-wire, halogen-free spiral cable, 2 wires shielded, draw length 1.5 m max., without connector
Operating elements	3 buttons, black, orange, green
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Former Item Number	01 6109 01700105 2109-052-000-05

Microphone

Frequency range	300 Hz to 6 kHz at -10 dB
Sensitivity	1.6 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -15 dB)

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.