TM210 TF Hand Microphone

Dynamic hand microphone with one button

Article Number

01 6113 10100003

Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Rugged chrome housing
- Durable spiral cable
- Extremely durable switching contacts

Scope of delivery

- Hand microphone with spiral cable

Options

- Protection against unintentional button presses
- Customized plugs and cables
- Special button colours or symbols
- Black housing
- Minor modifications and individual adaptations on request

Application range

- Radio system in mobile and fixed applications

Accessories

- HV5 mount
- WS16 windscreen
- Microphone preamplifier V966, V967, V856 and V857

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 10.09.2026 22:45

Specifications

General

Housing	Brass, silver
Dimensions	Length 178 mm, Ø 24 mm
Weight	215 g (7.6 oz)
Connection	4-wire, halogen-free spiral cable, 2 wires shielded, draw length 1.5 m max., without connector
Operating and display elements	1 button, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Former Item Number	01 6113 00100003 2113-001-000-03

Microphone

Frequency range	150 Hz to 12 kHz at -10 dB
Sensitivity	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -20 dB)

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.