

TM210 TFR Hand Microphone

Dynamic hand microphone with two buttons

Article Number

01 6113 00700003



Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Rugged chrome housing
- Durable spiral cable
- Extremely durable switching contacts

Scope of delivery

- Hand microphone with spiral cable

Options

- Protection against unintentional button presses
- Customized plugs and cables
- Special button colours or symbols
- Black housing
- [Minor modifications and individual adaptations](#) on request

Application range

- Radio system in mobile and fixed applications

Accessories

- HV5 mount
- WS16 windscreen
- Microphone preamplifier V966, V967, V856 and V857

Specifications

General

Housing	Brass, silver
Dimensions	Length 178 mm, Ø 24 mm
Weight	230 g (8.1 oz)
Connection	6-wire, halogen-free spiral cable, 2 wires shielded, draw length 1.5 m max., without connector
Operating elements	2 buttons, orange, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Former Item Number	01 6113 00700003 2113-004-000-03

Microphone

Frequency range	150 Hz to 12 kHz at -10 dB
Sensitivity	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -20 dB)