

# TM310 Gooseneck Microphone

Dynamic gooseneck microphone with On/Off switch

## Article Number

01 6119 00000005



## Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Rugged housing with gooseneck
- Long-life slide switch
- Interference field compensation

## Scope of delivery

- Gooseneck microphone with cable

## Options

- [Minor modifications and individual adaptations](#) on request

## Application range

- Radio and PA system in mobile and fixed applications

## Specifications

### General

|                       |                                                              |
|-----------------------|--------------------------------------------------------------|
| Housing               | Brass, black                                                 |
| Gooseneck             | Steel coil with external brass winding, black                |
| Dimensions            | Length 792 mm, head Ø 29 mm, body Ø 24 mm, gooseneck Ø 15 mm |
| Weight                | 726 g (25.6 oz)                                              |
| Connection            | 4-wire cable, 2 wires shielded, 2.7 m, without connector     |
| Storage temperature   | -30 °C to +70 °C (-22 °F to +158 °F)                         |
| Operating temperature | -20 °C to +60 °C (-4 °F to +140 °F)                          |
| Operating elements    | ON/OFF switch (slide switch), black                          |

### Microphone

|                 |                                  |
|-----------------|----------------------------------|
| Frequency range | 300 Hz to 6 kHz at -10 dB        |
| Sensitivity     | 1.5 mV/Pa (-56 dBV/Pa ± 3 dB)    |
| Impedance       | 200 Ohm ± 20 % at 1 kHz          |
| Directivity     | Cardioid (at 1 kHz; 180° -15 dB) |