

DD112 TF Hand Microphone

Dynamic hand microphone with one button

Article Number

6208-004-000-02 (former 2208-002-000-02)



Characteristics

- Dynamic microphone capsule
- Rugged chromed housing
- Durable spiral cable
- Extremely durable switching contact
- Interference field compensation

Scope of delivery

- Hand microphone with spiral cable

Options

- Splash protection for microphone capsule
- Protection against unintentional button presses
- Customized plugs and cables
- Special button colours or symbols
- Black housing

Application range

- Radio and PA systems in mobile and fixed applications

Accessories

- HV5 mount
- Rubber protective ring for microphone head
- Microphone preamplifier V966, V967, V856 and V857

Specifications

General

Housing	Brass, silver
Dimensions	Length 142 mm, head Ø 29 mm, body Ø 24 mm
Weight	210 g (7.4 oz)
Connection	4-wire halogen-free spiral cable, 2 wires shielded, draw length 1.5 m max., without connector
Operating elements	1 button, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range	150 Hz to 4 kHz at -10 dB
Sensitivity	2 mV/Pa (-54 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Omnidirectional