HA8 Handset

Handset with one release button

Article Number

01 6506 17500051 (former 2506-175-000-51)

Characteristics

- Dynamic ear capsule
- Electret microphone capsule
- Solid plastic housing
- Durable PUR spiral cable
- Button for hook switch

Scope of delivery

- Handset with PUR spiral cable
- A8 cradle with screws

Options

- Customized plugs and cables
- Flame-resistant plastic housing
- Amplifier
- Push-to-talk button and force release mechanism
- Minor modifications and individual adaptations on request

Application range

- GSM applications
- Installations with limited space

Accessories

- A8 cradle with screws

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 26.04.2024 17:24

Specifications

General	
Housing	PC-ABS plastic, black
Dimensions	Height 35 mm, width 50 mm, depth 160 mm
Weight	190 g (6.7 oz)
Connection	5-wire, halogen-free spiral cable, 2 wires shielded, draw length 1.5 m max., RJ50 10-pin connector
Operating elements	1 release button, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-25 °C to +60 °C (-13 °F to +140 °F)

Microphone	
Operating voltage	1.5 V to 10 V (DC)
Frequency range	100 Hz to 10 kHz at -10 dB
Sensitivity (in LRGP)	2.5 mV/Pa (-52 dBV/Pa ± 3 dB) at 3 V/2 kOhm
Impedance	1.4 kOhm ± 20 % bei 1 kHz/RL = 2 kOhm
Directivity	Omnidirectional

Earpiece	
Frequency range	400 Hz to 4 kHz at -10 dB
Sensitivity	20 dBPa/V ± 3 dB (IEC 3.2 low-leak coupler)
Impedance	110 Ohm ± 20 % at 1 kHz
Maximum output	10 mW

pei tel Communications GmbH
Rheinstraße 15 A, 14513 Teltow
Phone: +49 (0)3328 9363-0, info@peitel.com, www.peitel.com

Änderungen und Irrtümer vorbehalten. Abbildungen ähnlich.
Specifications subject to change. Product may differ from Image.
Erstellungszeitpunkt / Creation time 26.04.2024 17:24