

TM170 Microphone Head

Dynamic microphone head

Article Number

01 6117 00110003 (former 2117-001-000-03)



Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Chromed housing
- Designed for gooseneck mounting

Scope of delivery

- Microphone head with cable

Options

- Black housing (Art. No.: 6117-001-100-05)
- Mounted on gooseneck
- [Minor modifications and individual adaptations](#) on request

Application range

- Desktop microphones in indoor applications

Accessories

- Various goosenecks and mounting brackets
- Microphone preamplifier V966, V967, V856 and V857
- WS16 windscreen

Specifications

General

Housing	Brass, silver
Dimensions	Length 50 mm, Ø 24 mm
Weight	70 g (2.4 oz)
Connection	2-wire cable shielded, 1.8 m, without connector
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range	150 Hz to 12 kHz at -10 dB
Sensitivity	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -20 dB)