

# TM660 Microphone Head

Dynamic microphone head

## Article Number

01 6114 00110003 (former 2114-001-000-03)



## Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Chromed housing
- Designed for gooseneck mounting
- Protected against metal dust (INTERCEPT) and splash-proof

## Scope of delivery

- Microphone head with cable

## Options

- Microphone preamplifier
- Black housing
- Mounted on gooseneck
- [Minor modifications and individual adaptations](#) on request

## Application range

- Radio and PA system in mobile applications
- Designed for use in large vehicles

## Accessories

- Various goosenecks and mounting brackets
- Microphone preamplifier V966, V967, V856 and V857

## Specifications

### General

|                       |   |
|-----------------------|---|
| Housing               | Brass, silver                                   |
| Dimensions            | Length 85 mm, Ø 29 mm                           |
| Weight                | 160 g (5,6 oz)                                  |
| Connection            | 2-wire cable shielded, 3.0 m, without connector |
| Storage temperature   | -25 °C to +70 °C (-13 °F to +158 °F)            |
| Operating temperature | -20 °C to +60 °C (-4 °F to +140 °F)             |
| Certifications        | DIN EN 50155:2018-05<br>DIN EN 45545-2:2016-02  |

### Microphone

|                 |                                  |
|-----------------|----------------------------------|
| Frequency range | 300 Hz to 8 kHz at -10 dB        |
| Sensitivity     | 1.5 mV/Pa (-56 dBV/Pa ± 3 dB)    |
| Impedance       | 200 Ohm ± 20 % at 1 kHz          |
| Directivity     | Cardioid (at 1 kHz; 180° -15 dB) |